



Slot bracket USB 3.0 pin header 19 pin + SATA 7 pin internal > 1 x USB 3.0-A + 1 x Multiport external

Description

This slot bracket by Delock can be installed into a standard PC slot and expands your system by an external Multiport. The Multiport interface is a combination of USB 3.0 and eSATAp, which offers a number of connecting options. Thus the Multiport enables you to connect devices, like e.g. Hubs, Card reader, external enclosure etc. with the following interface:

1. USB 3.0
2. USB 2.0
3. eSATAp (Power Over eSATA 5 V)
4. eSATA



Ref.	82977
EAN	4043619829774
Country of origin	China
Customs tariff number	84718000

Specification

- Connector: internal 1 x 19 pin USB 3.0 pin header female
+ SATA 7 pin
external 1 x USB 3.0-A female
1 x Multiport female
- Cable gauge: 28 AWG
- Current output: max. 900 mA per each USB port
- Voltage: 5 V
- Data transfer rate up to:
Super-Speed 5 Gb/s, High-Speed 480 MB/s
Full-Speed 12 Mb/s, Low-Speed 1.5 Mb/s, eSATA 3 Gb/s
- Downwards compatible to USB 2.0 and USB 1.1
- Cable length: ca. 45 cm (without connector)

System requirement

- PC with a free slot
- Mainboard with a free 19 pin USB 3.0 pin header connector and a free SATA port

Note: For operation of two devices at the same time, which require more than 900 mA for each device, you may need to connect an additional power supply for the connected device.

Package content

- Slot bracket

Package

- Delock poly bag